



AMERICAN

INDUSTRIAL

WEAR PADS

Wear Pad Part Number Breakdown

CWP V2 3 x 4

TYPE OF WEAR PAD

PWP, CWP, LWP, FWP
EG, LDWP, HDWP

PAD WIDTH

2", 3", 4", 5"
6", 8", 10", 12"

VELCRO OPTION

V1, V2

PAD LENGTH

Any length desired
for the application.

Polyester

Extra layer of protection
Model PWP

Felt

Good cut resistance.
Model FWP

Velcro

Allows for easy addition
and removal of wear pad,
1 or 2 inch
Model V1 & V2

Cordura®

Great protection from
abrasive surfaces
Model CWP

Dyneema®

Superior Strength using
the world's strongest fiber.
Best option for cut &
abrasion resistance. Light
Duty or Heavy Duty
Model LDWP or HDWP

Leather

Very rugged, good cut
resistance. Velcro not
available with leather.
Model LWP

Edge Guard

Helps protect the edges of
the sling
Model EG



EDGE GUARD



SEWN BUFFER PAD



VELCRO PAD



VELCRO PAD



INSIDE EYE
BUFFER



WRAPPED EYE



TUBULAR WEAR PAD



⚠ WARNING

The top cause of synthetic sling failure is cutting. When a sling is cut, property damage and personal injury or death could result. Wear pads can help reduce this problem by supplying a buffer between the load edge and the sling. Be sure to inspect wear pads for damage. If the wear pad is damaged, the sling may also be damaged.